

SC 40P 10.5' Sliding Table Saw



SPECIFICATIONS

- Ribbed Cast iron work table
- Anodized aluminum alloy carriage w locking
- Hardened steel guide ways
- Saw blade adjustment by hand wheels
- Readout for saw blade tilt
- Saw blade guard mounted to riving knife
- Independently powered scoring unit
- External setup on score saw
- Squaring frame w/ telescoping fence & flip-over stops
- Rip fence w/ eccentric locking & fine adj.
- Eccentric clamping
- Table w/ extension on out-feed side
- Self braking motor



ELECTRICAL DATA

- 230 V – 3 Ph – 60 Hz. 27 Amps.
- Automatic Start Delta Start

TECHNICAL DATA

• Squaring capacity	3260 mm	128"
• Cutting width on rip fence	1270 mm	50"
• Main table dimensions	940 x 560 mm	37 x 22"
• Main/ scoring blade max diameter	400/ 120 mm	16/ 4.72"
• Blade tilt	90-45°	90-45°
• Max. cutting height @ 90°/45°	138/98 mm	5.4/3.8"
• Saw blade speeds- Main/Scoring	4000 / 9200 rpm	4000 / 9200 rpm
• Diameter of dust extraction outlet at machine base	120 mm	4.75"
• Blade protection with dust extraction outlet	60 mm	2.35"
• Main blade motor power		10 hp - S6
• Scoring unit motor power		0.9 hp
• Machine weight		1,650 lbs
• Arbor Size (Main / Scoring)		1 / 3/4"
• Overall Machine Dimensions (stroke x width)	7100 x 5050 mm	280 x 199"

*** Main & dado blades not included; scoring unit complete with blade**