

XENIA 60 12.5' Sliding Table Saw



SPECIFICATIONS

- Cast iron work table
- High precision, anodized aluminum alloy carriage w/ steel guides
- Automatic scoring unit w/ 2 programmed axis positions
- Manual rise/fall & tilting of saw unit by hand wheel
- 2 mechanical digital readouts for blade positioning
- Squaring frame w/ telescoping fence & flip-over stops including quick positioning pins for angular cutting
- Independently powered scoring unit
- Score saw arranged for double blades
- Rip fence w/ fine adjustment & locking
- Table w/ extension on out-feed side
- Overhead saw guard with dust extraction (100 mm)
- Automatic brake on main motor



ELECTRICAL DATA

- 230 V – 3 Ph – 60 Hz
- Automatic Star Delta Starter

TECHNICAL DATA

| | | |
|--|--------------------|--------------------|
| • Squaring capacity w/ extended stop | 3800x 3200 mm | 126" x 126" |
| • Cutting width on rip fence | 1250 mm | 50" |
| • Main table dimensions | 940 x 560 mm | 37 x 22" |
| • Main/ scoring blade max diameter | 400 / 120 mm | 16 / 4.72" |
| • Blade tilt | 90-45° | 90-45° |
| • Max. cutting height @ 90°/45° (w/ 400 mm Ø blade) | 130 / 92 mm | 5.1 / 3.6" |
| • Main blade speed (3 speed) | 3000-4000-5000 rpm | 3000-4000-5000 rpm |
| • Scoring blade speed | 8500 rpm | 8500 rpm |
| • Diameter of dust extraction outlet at machine base | 120 mm | 5" |
| • Diameter of dust extraction outlet at hood | 100 mm | 4" |
| • Main blade motor power (s6) | | 11 Hp |
| • Scoring unit motor power | | 1.3 Hp |
| • Machine weight | | 2,705 lbs |
| • Arbor Size (Main/ Scoring) | | 1 / 3/4" |
| • Overall machine dimensions (stroke x width) | 7330 x 5330 mm | 288 x 210" |