



## Dust Collectors -- High Efficiency Models

Model **AF/2C (2-Bag Stationary)**  
 Model **AF/4C (4-Bag Stationary)**

### Standard Equipment

- 5.5 or 7.5 HP motor (depending on model) for connection at 220/440/3/60
- Motor starter switch
- Overload protection
- Multiple port inlets
- Lower plastic collection bags
- Upper filter bags

### Optional Equipment

- Stop gate
- Canvas collection bag
- Cartridge filter 500 mm diameter
- Single phase motor (HP on request)
- Adapter skirt for 55-gallon drum including one strap
- Optional inlet opening (2" x 5", 3" x 6")



**AF/4C**

### Specifications

	<b>AF/2C</b>	<b>AF/4C</b>
• Motor:	5.5 HP	7.5 HP
• RPM:	3400	3400
• AMPS @ 230 V:	15.4	22
• CFM*:	3930	5310
• Inlet opening:	250mm	315mm
• Filter surface	58 sq. ft	117 sq. ft
• No. Collection bags:	2	4
• Collection capacity:	18 Cu. Ft.	36 Cu. Ft.
• dB level:	89	95
• Dimensions:	65" x 26" x 114"	53" x 53" x 114"
• Weight:	285 lbs.	420 lbs.

**\* Measured at 4.5" static pressure**