

## Dust Collectors -- Portable Models



- Model **CA/1C (1 BAG)**
- Model **CA/2C (2 BAG)**
- Model **CA/3C (3 BAG)**
- Model **CA/4C (4 BAG)**

### Standard Equipment

- 3, 4, 5.5 or 7.5 HP motor (depending on model)
- For connection at 220/440/3/60
- Motor starter switch
- Overload protection
- Built-in air flow dampers
- Multiple port inlets (see below)
- Upper filter bags
- Lower plastic collection bags
- Four casters

### Optional Equipment

- Canvas collection bag
- Stop gate
- Cartridge filter 450 mm diameter (single bag model)
- Cartridge filter 500 mm diameter
- Single phase motors (HP on request)



### Specifications

	CA/1C	CA/2C	CA/3C	CA/4C
• Motor:	3 HP	4 HP	5.5 HP	7.5 HP
• RPM:	3400	3400	3400	3400
• AMPS @ 230 V:	9.6	11.2	15.4	22
• CFM*:	1890	2480	3180	3850
• dB level:	86	88	91	94
• Port inlet diameter:	3 x 5"	1 x 6", 2 x 5"	4 x 6"	2 x 5", 3 x 6"
• Main pipe diameter:	200 mm	220 mm	250 mm	280 mm
• Collection bags:	1	2	3	4
• Collection capacity:	9 Cu. Ft.	18 Cu. Ft.	27 Cu. Ft.	36 Cu. Ft.
• Dimensions:	47" x 21" x 108"	78" x 25" x 108"	104" x 30" x 108"	125" x 33" x 108"
• Weight:	155 LBS	235 LBS.	290 LBS.	400 LBS.

**\* Measured at 4.5" static pressure**