



Minimum Contact Disc Conveyors

FIN manufacturers both idle and motorized heavy-duty disc conveyors.



Motorized Model



Idle Model

Standard Features

- Frame is of steel construction for strength and durability (with optional casters)
- Stainless steel discs are 6" (150 mm) diameter and mounted 5 1/2" (120 mm) apart on roller shafts with sealed ball bearings on each end
- Galvanized water tray with drain valve for cleaning discs
- Gravity feed roller shafts
- Feed speed 66 FT/MIN (motorized version only)
- *Idle system* – 1300 mm x 2500 mm (4' x 8')
- *Idle system* – 1500 mm x 3000 mm (5' x 10')
- *Idle system* – 1500 mm x 3500 mm (5' x 12')
- *Motorized system* – 1300 mm x 2500 mm (4' x 8')
- *Motorized system* – 1500 mm x 3000 mm (5' x 10')
- *Motorized system* – 1500 mm x 3500 mm (5' x 12')

Options

- Speed variator (15 to 95 FT/MIN)
- Four casters
- Stainless steel water tray
- Electronic eye stop

Weights

- *Idle system* – 1300 mm x 2500 mm (4' x 8')..... 865 lbs
- *Idle system* – 1500 mm x 3000 mm (5' x 10')..... 1000 lbs
- *Idle system* – 1500 mm x 3500 mm (5' x 12')..... 1450 lbs
- *Motorized system* – 1300 mm x 2500 mm (4' x 8')..... 965 lbs
- *Motorized system* – 1500 mm x 3000 mm (5' x 10')..... 1100 lbs
- *Motorized system* – 1500 mm x 3500 mm (5' x 12') 1550 lbs