

## Two Roller Glue Spreader

### SC2R 1300 or SC2R 1600



Heavy duty, top and bottom two roller glue spreaders with doctor blade and galvanized glue tank.



### Standard Features

- Heavy duty construction
- Start and stop buttons, on/off indicator lamp, magnetic start, overload protection with double emergency stop bars
- 0.5 HP motor for connection at 230/460/3/60
- 185 mm Ø rollers, covered in special anti-acid rubber, precision ground and hard wearing, allowing up to 6-7 resurfacings, resulting in precise and uniform spreading of glue
- Special springs on the roller supports allow continuous feed of different panel thicknesses with a variance of up to 5 mm without resetting the machine
- Separate switch allows operator to use 2 rollers together or one at a time
- Self-adjusting chain drive
- 4 casters
- Net weight ..... 510 – 1200 lbs
- Maximum opening between rollers ..... 120 mm (4 ¾")
- Feed speed ..... 19 MT/MIN (63 FT/MIN)
- Shipping weight 1300 (51")..... 1105 lbs
- Shipping weight 1600 (63")..... 1400 lbs
- Other sizes (widths) available (pricing on request)
  - 300 – 400 – 600 mm (12" – 16" – 24")
  - 800 – 1000 (31" – 39")

### Options

- Manual cleaning device
- Automatic cleaning device
- Speed variator, from 15 - 75 FT/MIN
- Single-sided fixed infeed fence
- Double-sided (right side fixed, left side adjustable) infeed fence
- Spare rollers (12" – 24") each
- Spare rollers (31" – 30") each
- Spare rollers (51") each
- Spare rollers (63") each