



Four Roller Glue Spreader

Model **SC4/98**

Heavy-duty, top and bottom four roller glue spreaders with two doctor rollers and galvanized glue tank. Available in the following widths:

- 1300
- 1400
- 1600
- 2000



Standard Features

- Heavy duty construction
- Start and stop buttons, on/off indicator lamp, magnetic start, overload protection with double emergency stop bars
- Two 0.9 HP motors for connection at 230/460/3/60
- 2 spreading rollers 250 mm Ø, covered in special anti-acid rubber, precision ground and hard wearing, allowing up to 6-7 resurfacings
- 2 ebonite doctor rollers 190 mm Ø allow precise and uniform spreading of glue by rotating at a slower speed than the spreading rollers. When the spreading rollers come in contact with each other, a free-wheeling device eliminates overheating and excess wear of the rubber. Accurate dosage is possible adjusting the distance between the doctor rollers by means of a hand wheel and endless screw adjustment.
- Special springs on the roller supports allow continuous feed of different panel thicknesses with a variance up to 5 mm without resetting the machine
- Anti-accident devices on the spreading and dosing rollers include double emergency bars (front and back). If the spreading roller and dosing rollers are touching, they will stop when the protection grid is lifted up. If they are not touching each other, they will reverse direction, therefore assuring maximum safety to the operator.
- Separate switch allows operator to use 2 rollers together or one at a time
- Self-adjusting chain drive
- 4 casters
- Net weight 2000-2900 lbs
- Maximum opening between rollers 120 mm (4 ¾")
- Feed speed 19 MT/MIN (63 FT/MIN)

Options

- Speed variator with inverter
- Automatic washer
- Motorized raising of the roller with visual display
- Motorized infeed rollers