

Top & Bottom Cross Belt Panel Cleaner *

ST 1300 or ST 1600



This machine features a unique cleaning system with top and bottom brushes that work across the surface of the panel, eliminating the common problem of dust being redeposited on the panel surface by rotating brushes. It is particularly suitable for panel cleaning before glueing, polishing, and painting. The brushes do not require replacement or changing between different types of cleaning.



Technical Specifications

	ST 1300	ST 1600
• Working width	1300 mm (51")	1600 mm (63")
• Maximum thickness	90 mm (4")	90 mm (4")
• Dust hood diameter	220 mm (9")	220 mm (9")
• CFM requirement	2060 CFM	2060 CFM
• Upper brush motor	1 HP	1 HP
• Lower brush motor	1 HP	1 HP
• Feed motor	1 HP	1 HP
• Variable feed speed	45/135 FT/MIN	45/135 FT/MIN
• Feed speed for cleaning brushes	180 FT/MIN	180 FT/MIN
• Net weight	1000 KG (2200 lbs.)	1200 KG (2640 lbs.)
• Dimensions	228" x 100" x 165"	262" x 100" x 165"
• Number of brushes	98	112

Options

- Optional casters
- Motorized raising/lowering of upper brush group
- Motorized entry rollers
- Motorized exit rollers
- Variable feed speed for each
- Antistatic brushes
- Replacement brushes each
- Double sided (right side fixed, left side adjustable) infeed fence

*** Special Machine**