

Blitz 2.0

CNC DRILLING GLUING DOWEL INSERTING MACHINE – 3 controlled axes (X, Y, Z). Highly efficient and reliable thanks to simple software. Ideal for "JUST IN TIME" production or mass production. Blitz, the necessary complement for horizontal & vertical drilling execution in "nesting" philosophy.

STANDARD FEATURES

- 3 horizontal independent spindles
- 3 vertical independent spindles
- 1 glue and dowels inserting unit
- 1 high capacity vibrator to feed the dowels
- 2 working areas
- 2 side reference stops (dx, sx) on the working table
- 1 central reference stop on the working table
- 4 clamps

Drilling Head:

- 3 independent horizontal spindles at 3500 speed/min
- 3 independent vertical spindles at 3500 speed/min

Working Area Horizontal Head

- X= 1300 mm
- Y= 50 mm
- Z= 50mm

Inserting Glue & Dowel Unit:

- 1 glue and dowel injector. Dowel dimension: min 6x25mm; Max 10x40mm

Glue System:

- 1 glue tank "underpressure" lt 18
- 1 water tank "for cleaning" lt 9

Hardware & Software

- 19" LCD TFT monitor
- PC Windows system
- TPA software
- USB port for loading programs



CE STANDARDS

OPTIONS

- Medium pressure glue system pump
- Bar code reader
- 45° stop