



Shaper / Profile Sander *

LS-1NR

Standard Features

- Stackable spindle (up to 3 cutters) on shaper station
- One variable speed (1-7500 RPM) 360° tilting station for sanding or shaping application
- One sanding belt station with 135° of tilt and ¾" vertical oscillation
- 3 ¼" x 96 ½" sanding belt
- 6 HP motor on shaper station
- 2 HP motor on sanding belt station
- 2 HP motor powers feed belt drive for automatic feed
- Variable feed speed (0-81 FT/MIN)
- Reverse feed feature
- Air blowers for sanding belt cleaning
- CE guards



Options

- Mechanical digital readouts, each station
- Hard felt block with aluminum support
- Steel block, predrilled for air cushion and pre-shaped at factory

Specifications

- Shaper motor..... 6 HP
- Shaper speed (variable) 1-7500 RPM
- Sanding belt motor (2 speed) 2 HP
- Sanding belt speeds (two) 22 ¾ / 45 ½ FT/SEC
- Maximum tooling diameter..... 6 ¼" (160 mm)
- Belt width..... 6"
- Feeding speed (variable)..... 0-81 FT/MIN
- Maximum height of work piece 4 ¼"
- Minimum length of work piece 4"
- Shaper spindle diameter..... 35 mm (1 ¼" on request)

Overall Dimensions

- Net weight 2050 lbs
- Gross weight 2300 lbs
- Packing size 142" x 55" x 75"

*** Special Machine**